


H05VV-F Round PVC Cable Black



- Cable

: PVC insulated multi core flexible installation and automotive cables
- 1) Conductor

: Flexible plain copper, massive
- Construction

2) PVC insulation
4) PVC Sheath
- According to EN 50525-2-11 and IEC 60227.5
- Temperature range

: -15 °C up to 60 °C
- Max conductor Temperature

: 50 C
- Maximum Voltage

: 300/500V
- Test Voltage (AC)

: 2 kV
- Cable Marking

: H05VV-F __mm² BS6500 jaartal
- Minimum bending radius

: 5 x D
- Core insulation color

: 2 cores ; Black / Red
: 3 cores ; Black / Red / White,
: 5 cores ; Brown / Grey / Red / White / Yellow



STANDARD
TS EN 50525 2-11

TECHNICAL AND ELECTRICAL PROPERTIES PVC BLACK

Article number	Cores	Quadrature [mm²]	intersection [mm]	iR @ 20 °C [Ω/km]	Current [A]	Weight Cable [kg/km]	Roll Length [m]
30-29450	2	0,75	6,20	26,00	8	54,80	100
30-29484	2	1,50	7,50	13,30	10	84,80	100
30-29485	2	2,50	9,10	7,98	16	129,00	100
30-29452	3	0,75	6,60	26,00	8	65,05	100
30-29468	3	1,50	8,20	13,30	10	107,00	100
30-29478	3	2,50	9,90	7,98	16	161,00	75
30-29525	5	2,50	12,00	7,98	16	249,00	50

